FXP (POWER ROLLER FLEX)



E24N POWERED FLEXIBLE ROLLER CONVEYOR

Hytrol's FXP conveyor provides optimal conveying power and can easily be moved where it is needed most. The flexible, expandable conveyor will stretch or bend to fit your available space and is ideal for truck loading and unloading areas, distribution centers or portable assembly lines.



EFFICIENT

The FXP is a sturdy conveyor that moves product up to 100 lbs. per E24N motor at variable speeds and each zone is powered by an energy efficient Hytrol E24N (24-volt) motor.

SMART

Networked controls and pass-through power cables can connect multiple units to the FXP. Includes start/stop buttons along with forward/reverse controls. Complete with full lane photoeye.

SAFE

The FXP operates at 60dB, (approximately 5 ft. 6 in. from ground level) to protect the hearing of operators. The conveyor stays where it's needed with powder coated leg supports with locking, swivel casters and pin-adjustable heights.

FLEXIBLE

The name says it all. This Powered Roller Flex Conveyor can compress or extend up to 80 feet and be moved into configurations that meet various needs.



SPECIFICATIONS



• LOAD CAPACITY	50 lbs. per linear foot (PLF)/
	100 lbs. per E24N motor
• EXTENDED LENGTH	40 ft., 60 ft., 80ft.
• CONVEYOR HEIGHT	Height A = 30" TOR - Adjustable 24-34" TOR
	Height B = 34" TOR – Adjustable 30-38" TOR

• **CONVEYOR WIDTH** ----- 24 in., 30 in.

• ROLLERS ----- 1.4 in. or 1.9 in.; expanded roller distance varies

• **POWERED BY** ----- E24N (24VDC) motor

• WARRANTY ----- 1 Year





Hytrol sells exclusively through our Integration Partner Network which consists of over 150 independent businesses worldwide. These experts can assist with material handling projects of all shapes and sizes. Visit hytrol. com today to be matched with an integrator near you.